

Witness Production Performance at its Very Best . . .

from

• **SEAL-TRON** •

Corporation™

OCONO OT-1910-66 Shrink Tunnel



Featuring:
Dual-Shrink Zone and
ADJUSTA™ Stand

Shrink Tunnel Standard Features :

- SURROUND AIR™
- KOOL-TUCH™
- ADJUSTA™ Stand with Locking Casters
- Solid State Temperature Controller
- Cool-Down Cycle
- Dual Chamber 66" long

Shrink Tunnel Optional Features :

- Glass Filled Nylon Belt
- Long Life TFE Covered Rollers
- Close Roller Spacing
- Matching Exit Conveyor
- Secondary Cooling Fan for Poly
- TPF, Thin Package Fixture

BUILT FOR SERIOUS PERFORMANCE

Economical and Powerfull for high speed Applications

OCONO Shrink Tunnel

Technical Specifications:

Model:	OT-1910-66
Tunnel Chamber:	19"W x 10"H x 66"L
Power Requirements:	208/240 VAC - 45/50A 3 PH
Shipping Weight:	1000 lbs
Shipping Size:	36"W x 80"H x 80"L
Roller Diameter:	5/8" including the silicone cover

□ We call our thermal system "Surround-Air™" - an exclusive network that distributes hot air evenly to every square inch of your package. You get a clean, uniform shrink on every side - including the bottom. This OCONO series shrink tunnel features a special pre-shrink section in the entrance of the tunnel chamber, allowing the bottom of the package to be shrunk first. This is helpful to arrange your package seals on the bottom of the package. A unique baffling system enables the operator to adjust the air flow to allow even the lightest package to pass through the chamber.

□ High wattage 3" diameter coiled long life Calrod heaters heat quickly and recover rapidly between the on/off cycle. A solid state temperature controller with solid state power switching regulates the tunnel heat reliably to $\pm 2^{\circ}\text{F}$. When the machine is turned off, the cool-down cycle engages, disconnecting the heaters while the conveyor and blower continue to run until the tunnel chamber temperature has reached a safe level assuring long component life.

□ The heavy duty variable speed DC motor pulling 1/2" diameter rollers on a heavy duty #40 x 3/4 D3 pin chain. Our standard Silicone Rubber covered rollers may be replaced with long life TFE Teflon covers. A GFN "Glass Filled Nylon" belt is available for specific applications. Check with your distributor or a SEAL-A-TRON™ representative regarding your particular application for additional details.

□ By isolating the interior walls from the outside walls, we achieved a substantially cooler tunnel exterior! KOOL-TUCH™! All exterior parts of the tunnel are cool to the touch.

□ The unique Adjusta Stand allows the operator to level the infeed height of the tunnel with the discharge height of the product take away conveyor of the sealer. Our specially designed optional exit conveyor with 1" aluminum rollers on a 1.5" center fits precisely at the end of the tunnel and allows even the lightest product to clear the tunnel.



The Control Panel is located above the infeed of the Shrink Tunnel to be operated from both sides.

Seal-A-Tron offers a 1-year warranty on all equipment

"Quality Second To None at a Price You Can Afford"

SEAL-A-TRON™ Corporation • 3815 S.E. Naef Road • Portland, OR 97267 • Phone (503) 652-5200 • Fax (503) 905-1331

Come visit us on the Internet at: www.seal-a-tron.com / e-mail sales@seal-a-tron.com