

A **BOLD** new look with solid Performance

from

• **SEAL-A-TRON** •

Corporation™

5



S-SERIES L-Bar Sealers

L-Bar Sealer Standard Features :

- Dual **MAG-LOK™** easy adjustable Magnetic Hold-Down (1)
- Anodized Aluminum Seal-Head with Film Clamps (2)
- TRU-TEMP™** Digital Seal Wire Control (3)
- EZ-PERF™** Venting System with reduced Friction (4)
- Large Heavy Duty Film Dispenser with **POSI-GUIDES™** (5)
- Heavy Duty Console Stand with Locking Casters & Shelf (6)
- Product Discharge Conveyor with Soft Start Vari-Speed
- Large Head opening for Easy Insertion of Taller Products

L-Bar Sealer Optional Features :

- PFU, Power Film Unwind with **ADJUSTA™** Inverting Head
- Heavy Product Discharge Conveyor with Rollers under Belt
- Pneumatic Head Down
- Stainless Steel Film Separator
- Roller Infeed Loading Tray
- Stainless Steel Infeed Loading Tray
- Maintenance Kit
- Bumper to Prevent Sealer Jamming into Shrink Tunnel

BUILT FOR SERIOUS PERFORMANCE

Versatility and Performance with Lots of Features

S-SERIES L-Bar Sealers

Technical Specifications :

MODEL NO.:	S-1620	S-2330	S-2336	S-2348	S-2372
SEAL AREA:	16"x20"	23"x30"	23"x36"	23"x48"	23"x72"
SHIPPING WEIGHT:	680 lbs	860 lbs	900 lbs	1200 lbs	1400lbs
SHIPPING SIZE:	86"Lx48"Wx60"H	102"Lx55"Wx60"H	102"Lx55"Wx60"H	120"Lx55"Wx60"H	140"Lx55"Wx60"H

Machine Footprint **52"Lx32"Wx52"H** **90"Lx48"Wx52"H** **88"Lx48"Wx52"H** **96"Lx56"Wx52"H** **126"Lx48"Wx52"H**

MODEL NO.:	S-3230	S-3236	S-3248	S-3272
SEAL AREA:	32"x30"	32"x36"	32"x48"	32"x72"
SHIPPING WEIGHT:	960 lbs	1000 lbs	1400 lbs	1600 lbs
SHIPPING SIZE:	102"Lx68"Wx60"H	102"Lx68"Wx60"H	120"Lx68"Wx60"H	140"Lx68"Wx60"H

Machine Footprint **90"Lx56"Wx52"H** **90"Lx56"Wx52"H** **102"Lx56"Wx52"H** **126"Lx56"Wx52"H**

SEAL-A-TRON™'s S-SERIES™ L-Bar Sealers are built for heavy-duty service and continuous operation. The **S-SERIES™** L-Bar Sealers are loaded with features :

- ◆ Extra durable seal-head (anodized aluminum)
- ◆ Special composite beads as seal wire insulator
- ◆ Anti-rotation, anti-twist seal wire take-up connector
- ◆ Technologically advanced, reliable solid state **TRU-TEMP™** Digital PC logic seal-wire control
- ◆ **EZ-PERF™** film perforator with heavy duty **POSI-GUIDES™** film roll guidance system
- ◆ Permanent heat-sink at each seal wire to ensure long life
- ◆ **MAG-LOK™**, the industry's strongest magnets with easy-adjust pad for quick tuning of seal pressure
- ◆ Quick-adjust product height adjustment
- ◆ Sturdy console stand with locking casters
- ◆ Heavy-duty product take-away conveyor
- ◆ Storage shelf for storing rolls of film

Shrink films have changed considerably in the past few years, yet most hardware manufacturers have failed to keep pace. The films are becoming clearer, tougher and more complex. A quality sealing system must be able to produce a seal at least as strong as the film itself.

We at **SEAL-A-TRON™** recognize this and consequently equip our **S-SERIES™** models with our hard chrome anodized aluminum seal-head, designed to withstand heavy seal pressure from our extra powerful magnets. Seal wires are insulated with a hi-temp, coated composite bead. The temperature is accurately controlled by our proven **TRU-TEMP™** digital circuit board. Careful design of durable parts assure a constant, quality seal unmatched for strength and consistency.

Optional:
30" PFU,
Power Film Unwind



SEAL-A-TRON offers a 1-year warranty on all equipment .

“Quality Second To None at a Price You Can Afford”

SEAL-A-TRON™ Corporation • 3815 S.E. Naef Road. • Portland, OR 97267 • Phone (503) 652-5200 • Fax (503) 652-5205
Come visit us on the Internet at: www.seal-a-tron.com / e-mail sales@seal-a-tron.com