



Available in 24", 30", 36", 42" Seal Bar Lengths

Standard Features:

Electronic Seal Stroke Seal Head (NO COMPRESSED AIR NEEDED)

- Package Speeds Up to 10 Packages Per Minute
- Electronic Seal Stroke Seal Head (NO COMPRESSED AIR NEEDED)
- 16" Seal Height Stroke which is Electronically Adjustable
- Manual Slide Pushing Plate with Adjustable Guides
- PLC Driven Controls / 6" HMI Touch Screen
- V-Grooved Belted Exit Conveyors
- Side Mounted Top Film Unwind for ease of Loading Film
- Slide-Out Lower Film Cradles
- Permanently Heated Seal-Head, with Solid State Digital Temp Controllers,
 High-Temp Alarm, Mushroom Blade Insert with Heavy Duty TFE Teflon Coating
- 1/2" Plexiglas Doors with Safety Switches
- Heavy Duty Construction with Leg Leveling Pads
- Power Require 220 VAC, Single Phase 25 amps

Options:

- Light Package Hold Down (Requires Compressed Air)
- Additional Seal Height for Tall Product



PREMIUM MACHINERY at a Reasonable Price!

Seal-A-Tron Corporation™ • 3815 S.E. Naef Road. • Portland, OR 97267 • Phone (503) 652-5200